















	PRODUCT SYSTEM	CATEGORY	MIX RATIO	READY FOR USE VOC (when mixed as directed)	NATIONAL RULE CATEGORY LIMIT	NATIONAL RULE COMPLIANT
TOPCOATS	ULTRA-GLO Acrylic Urethane	Topcoat Single stage	3:1 with Activator (UA-1600M/UA-1600S)	4.61 - 4.93 lbs/gallon	5.0 lbs/gallon (599 grams/liter)	
	SPECTRA Series Urethane Candy	Topcoat Single stage	4:1 with Activator (0175)	4.78 lbs/gallon	5.0 lbs/gallon (599 grams/liter)	
	ACRYL-GLO Acrylic Enamel	Topcoat Single stage	8:2:1 with A/E Reducer and Hardener (K-1606/K-1607)	4.77 - 4.99 lbs/gallon	5.0 lbs/gallon (599 grams/liter)	
	SYN-GLO Synthetic Enamel	Topcoat Single stage	8:2:1 with S/E Reducer and Hardener (K-1605)	4.61 - 4.86 lbs/gallon	5.0 lbs/gallon (599 grams/liter)	
CLEAR COATS	ULTRA H/S Urethane Clear	Topcoat Clear coat	4:1 with H/S Clear Activator (3065/3075/3085)	4.23 lbs/gallon	5.0 lbs/gallon (599 grams/liter) *	
	EUROTHANE H/S Urethane Clear	Topcoat Clear coat	2:1 with H/S Clear Activator (ECA200F/ECA200S)	4.66 lbs/gallon	5.0 lbs/gallon (599 grams/liter) *	
	CUSTOM H/S Urethane Clear	Topcoat Clear coat	4:1 with Activator (0175)	4.33 lbs/gallon	5.0 lbs/gallon (599 grams/liter) *	
	PRO-FLO M/S Urethane Clear	Topcoat Clear coat	4:1 with M/S Clear Activator (0065/0075/0085)	4.79 lbs/gallon	5.0 lbs/gallon (599 grams/liter) *	
	ZOOM High Speed Urethane Clear	Topcoat Clear coat	4:1 with M/S Clear Activator (0065/0075/0085)	4.16 lbs/gallon	5.0 lbs/gallon (599 grams/liter) *	
PRIMERS	PERFECT PRIME 2K Urethane Primer Surfacer	Primer Surfacer	4:1 with Activator (UPC73)	4.53 lbs/gallon	4.8 lbs/gallon (575 grams/liter)	
	RAPID PRIME 2K Urethane Primer Surfacer	Primer Surfacer	4:1 with Activator (UPC711)	4.39 lbs/gallon	4.8 lbs/gallon (575 grams/liter)	
	ENDURO PRIME DTM Epoxy Primer	Primer	1:1 with Catalyst (EPC611)	4.78 lbs/gallon	4.8 lbs/gallon (575 grams/liter)	
	SUPER RUST STOP Non-Sanding DTM Primer	Primer	4:1 with A/E Reducer	4.75 lbs/gallon	4.8 lbs/gallon (575 grams/liter)	
	ACRYLIC HIGH BUILD Lacquer Primer Surfacer	Primer Surfacer	1:1 with Low-VOC Lacquer Thinner	4.44 lbs/gallon	4.8 lbs/gallon (575 grams/liter)	

* National Rule limits for Basecoat/Clearcoat systems (5.0 lbs/gallon) are calculated as VOC of Basecoat + (2 X VOC of Clear coat) / 3